



# GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

**Product name:** 2300-2700MHz Panel Antenna

**Product model:** GL-DY2327S6515

**Applications:**

4G /LTE System

Sector coverage

**Features:**

bandwidth,Low VSWR

Strong structure and simple installation



Electrical Specifications	
Frequency Range-MHz	2300-2700
Polarization	±45°
VSWR	≤1.5
Gain- dBi	15
Horizontal beam width	65°
Verticalbeam width	15°
Front-to-back ratio-dB	≥25
Isolation between ports-dB	≥28
Input Impedance-Ω	50
Maximum input power- W	100
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	2xN-K
Connector place	Bottom
Dimensions -mm	500×128×56
Packing size -mm	600×230×160
Antenna weight- kg	1.6
Radome material	UPVC
Radome color	Gray
Mechanical tilt	0~12°
Operating temperature	-40°C to +65 °C
Rated Wind Velocity- m/s	60
Mounting hardware- mm	φ 35~ φ 75

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.

Tel: 86-371-60911368 Email:info@global-antenna.com

Web:<http://www.asialeren.com> <http://www.global-antenna.com>