



# GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

**Product name:** 2300-2700MHz Panel Antenna

**Product model:** GL-DY2327S9011

**Applications:**

4G /LTE System  
Sector coverage

**Features:**

bandwidth,Low VSWR  
Strong structure and simple installation



Electrical Specifications	
Frequency Range-MHz	2300-2700
Polarization	±45°
VSWR	≤1.5
Gain-dBi	11
Horizontal beam width	90°
Verticalbeam width	30°
Front-to-back ratio-dB	≥23
Isolation between ports-dB	≥28
Input Impedance-Ω	50
Maximum input power- W	100
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	2xN-K
Connector place	Bottom
Dimensions- mm	230×128×56
Packing size- mm	330×230×160
Antenna weight- kg	1.1
Radome material	UPVC
Radome color	Gray
Mechanical tilt	0~12°
Operating temperature	-40°C to +65 °C
Rated Wind Velocity-m/s	60
Mounting hardware-mm	Φ 35~ Φ 75

Add: Room826, Floor 8,BLDG 13, University Science Park(East), Zhengzhou City, P.R.Henan, China.  
Tel: 86-371-60911368 Email:info@global-antenna.com  
Web:<http://www.asialeren.com> <http://www.global-antenna.com>