



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name: 2300-2700MHz Panel Antenna

Product model: GL-DY2327S9014

Applications:

4G /LTE System
Sector coverage

Features:

bandwidth,Low VSWR
Strong structure and simple installation



| Electrical Specifications | |
|------------------------------|-----------------|
| Frequency Range-MHz | 2300-2700 |
| Polarization | ±45° |
| VSWR | ≤1.5 |
| Gain-dBi | 14 |
| Horizontal beam width | 90° |
| Verticalbeam width | 15° |
| Front-to-back ratio- dBi | ≥23 |
| Isolation between ports -dBi | ≥28 |
| Input Impedance-Ω | 50 |
| Maximum input power -W | 100 |
| Lightning protection | DC Ground |
| Mechanical Specifications | |
| Input connector type | 2xN-K |
| Connector place | Bottom |
| Dimensions -mm | 500×128×56 |
| Packing size- mm | 600×230×160 |
| Antenna weight- kg | 1.5 |
| Radome material | UPVC |
| Radome color | Gray |
| Mechanical tilt | 0~12° |
| Operating temperature | -40°C to +65 °C |
| Rated Wind Velocity- m/s | 60 |
| Mounting hardware -mm | ∅ 35~ ∅ 75 |

Add: Room826, Floor 8,BLDG 13, University Science Park(East), Zhengzhou City, P.R.Henan, China.
Tel: 86-371-60911368 Email:info@global-antenna.com
Web:<http://www.asialeren.com> <http://www.global-antenna.com>