



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name: 2300-2700MHz Panel Antenna

Product model: GL-DY2327V9016

Applications:

4G /LTE System
Sector coverage

Features:

bandwidth,Low VSWR
Strong structure and simple installation



Electrical Specifications	
Frequency Range-MHz	2300-2700
Polarization	Vertical
VSWR	≤1.5
Gain -Bi	16
Horizontal beam width	90°
Verticalbeam width	7.5°
Front-to-back ratio-dB	≥23
Input Impedance-Ω	50
Maximum input power-W	100
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	N-K
Connector place	Bottom
Dimensions-mm	950×128×56
Packing size-mm	1050×230×160
Antenna weight-kg	3
Radome material	UPVC
Radome color	Gray
Mechanical tilt	0~15°
Operating temperature	-40°C to +65 °C
Rated Wind Velocity-m/s	60
Mounting hardware-mm	Φ 35~ Φ 75

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.
Tel: 86-371-60911368 Email:info@global-antenna.com
Web:<http://www.asialeren.com> <http://www.global-antenna.com>



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.
Tel: 86-371-60911368 Email:info@global-antenna.com
Web:<http://www.asialeren.com> <http://www.global-antenna.com>
