



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name: 2300-2700MHz Panel Antenna

Product model: GL-DY2327VH6512

Applications:

4G /LTE System
Sector coverage

Features:

bandwidth,Low VSWR
Strong structure and simple installation



Electrical Specifications	
Frequency Range-MHz	2300-2700
Polarization	Vertical + Horizontal
VSWR	≤1.5
Gain-dBi	12
Horizontal beam width	65°
Verticalbeam width	30°
Front-to-back ratio-dB	≥25
Isolation between ports-dB	≥28
Input Impedance-Ω	50
Maximum input power-W	100
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	2xN-K
Connector place	Bottom
Dimensions-mm	230×128×56
Packing size-mm	330×230×160
Antenna weight-kg	1.1
Radome material	UPVC
Radome color	Gray
Mechanical tilt	0~12°
Operating temperature	-40°C to +65 °C
Rated Wind Velocity-m/s	60
Mounting hardware-mm	Φ 35~ Φ 75

Add: Room826, Floor 8,BLDG 13, University Science Park(East), Zhengzhou City, P.R.Henan, China.

Tel: 86-371-60911368 Email:info@global-antenna.com

Web:<http://www.asialeren.com> <http://www.global-antenna.com>