



# GLOBAL EAST ASIA TECHNOLOGY CO., LIMITED

**Product name:**

**2500-2700MHz Fiberglass Omni Antenna**

**Product model: GL-DY2600V11**

**Applications:**

4G-LTE System

Point to multipoint application

**Features:**

HighGain, Stable Performance

HighQuality FiberglassRadome

All Weather Operation



| Electrical Specifications |            |
|---------------------------|------------|
| Frequency Range- MHz      | 2500-2700  |
| VSWR                      | ≤1.8       |
| Gain- dBi                 | 11         |
| Horizontal beam width     | 360°       |
| Verticalbeam width        | 7°         |
| Polarization              | Vertical   |
| Input Impedance-Ω         | 50         |
| Maximum input power- W    | 50         |
| Lightning protection      | DC Ground  |
| Mechanical Specifications |            |
| Input connector type      | N-K        |
| Connector place           | Bottom     |
| Dimensions- mm            | Φ20×915    |
| Antenna weight- kg        | 1.1        |
| Radome material           | Fiberglass |
| Radome color              | gray       |
| Operating temperature     | -40°c~60°c |
| Rated Wind Velocity- m/s  | 60         |
| Mounting hardware- mm     | Φ 35~ Φ 60 |

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.

Tel: 86-371-60911368 Email:info@global-antenna.com

Web:<http://www.asialeren.com> <http://www.global-antenna.com>