



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name: 3300-3800MHz Panel Antenna

Product model: GL-DY3338S6517

Applications:

5G Network System

Sector coverage

Features:

High gain, bandwidth

Strong structure and simple installation



Electrical Specifications	
Frequency Range- MHz	3300-3800
Polarization	±45°
VSWR	≤1.5
Gain- dBi	17
Horizontal beam width	65°
Verticalbeam width	7.5°
Front-to-back ratio- dB	≥25
Isolation between ports- dB	≥28
Input Impedance-Ω	50
Maximum input power- W	100
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	2xN-K
Connector place	Bottom
Dimensions- mm	650×128×56
Packing size- mm	750×230×160
Antenna weight-KGS	2.7
Radome material	UPVC
Radome color	Gray
Mechanical tilt	0~12°
Operating temperature	-40°C to +65 °C
Rated Wind Velocity- m/s	60
Mounting hardware- mm	φ 35~ φ 75

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.
 Tel: 86-371-60911368 Email:info@global-antenna.com
 Web:<http://www.asialeren.com> <http://www.global-antenna.com>