



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name: 698-2700MHz Panel Antenna

Product model: GL-DY7027S6512

Applications:

4G /LTE System
Sector coverage

Features:

bandwidth,Low VSWR
Strong structure and simple installation



Electrical Specifications	
Frequency Range- MHz	698-960/1710-2700
Polarization	±45°
VSWR	≤1.5
Gain- dBi	10/12
Horizontal beam width	65°
Verticalbeam width	50°/35°
Front-to-back ratio- dB	≥25
Isolation between ports- dB	≥26
Input Impedance-Ω	50
Maximum input power- W	100
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	2-7/16DIN Female
Connector place	Bottom
Dimensions- mm	700×325×145
Antenna weight- kg	7.5
Radome material	UPVC
Radome color	Gray
Mechanical tilt	0~12°
Operating temperature	-40°C to +65 °C
Rated Wind Velocity- m/s	60
Mounting hardware- mm	Φ 35~ Φ 75

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.
Tel: 86-371-60911368 Email:info@global-antenna.com
Web:<http://www.asialeren.com> <http://www.global-antenna.com>