



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product Name:LPDA Antenna

product model: GL-DY7038V11

Applications:

2G/3G/4G/5G/WLAN Wireless System.

Features:

1.Broadband;

2.Sealed with radome, Strong protection ability.



LPDA Antenna	
Electrical Index	
Frequency-MHz	698-960MHz/1710-2700MHz/3300-3800MHz
Gain-dBi	11dbi
VSWR	<2.0≤2.0/1.5/2.2
Input Impedance -Ω	50
Polarization	Vertical
Horizontal beam width	90°
Vertical beam width	60°
Front-to-back ratio	≥15dB
Intermodulation IM3 (2x33dBm)	≤-150dBc
Maximum input power	50W
Lightning protection	DC Ground

Mechanical Specifications	
Input connector type	N-K
Installation	Pole-holding
Dimensions	440×210×65mm
Antenna weight	0.85kg
Radiating Element Material	Al
Radome material	ABS
Operating temperature	-40°C to +65 °C
Mounting hardware	φ35~φ60
Rated Wind Velocity	60 m/s

Add: Room826, Floor 8,BLDG 13, University Science Park(East), Zhengzhou City, P.R.Henan, China.

Tel: 86-371-60911368 Email:info@global-antenna.com

Web: <http://www.asialeren.com> <http://www.global-antenna.com>