

# GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

4700-5000MHz 14dBi 65° 4T4R dual polarization sector panel antenna

PN: GL-W45PB6514FR

## Electronic Specifications

Frequency Range (MHz)	4700-5000
HW (°)	65±5
VW (°)	17±3
Gain (dBi)	14±1
Polarization	±45
VSWR	≤1.5
Port Isolation (dB)	≥25
F/B Ratio(dB)	≥23
Max Power (W)	50
Impedance(Ω)	50



## Mechanical Specifications

Dimensions(mm)	300×167×55
N.W(kg)	2
Rodome material	UPVC
Rodme Color	Gray
Connector Type	4×N female


## Environmental Index

Applications	Outdoor
Work Temperature (°C)	-40 to +70 (-40 to 158°F)
Humidity (%)	5 to 95
Max Velocity(km/h)	200

## Installation Parts

Pole Diameter (mm)	Φ 40 to 50
--------------------	------------

## Radiation Pattern



**Add:** Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China. Zip Code: 450051

**Tel:** 86-371-60911368

**Email:** [sales@global-antenna.com](mailto:sales@global-antenna.com)

**Web:** <https://www.global-antenna.com>