



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED
<http://www.global-antenna.com>



Use this antenna together with the Fatshark Dominator 5.8GHz receiver for daily flights on site

5.8G Antenna	
GL5800-05	
Electrical Index	
Frequency-MHz	5700-5900
VSWR	<1.5
Nominal Impedance-Ω	50
Polarization	RHCP
Gain-dBi	5
Beamwidth	110
Mechanical Index	
Cable Length	---
Connector	SMA male
Antenna Dimension-mm	35*35
Installation Way	---
Vibration	10 to 55Hz with 1.5mm amplitude 2hours
Environmentally Friendly	ROHS Compliant
Temperature-℃	-40~+85
Humidity-%	5~95

The beam width allows this patch antenna to be directly installed on your video glasses receiver. The typical range of this antenna is very comfortable at 1.5km on a 200mW transmitter (if we use the same metrics as our competitors, it converts to 3-4km). Therefore, it matches or exceeds all existing Cloverleaf/Skew-Planar-Wheel combinations, but it only has a coverage range of 110 degrees. It is more durable and lighter than other receiving race antennas.

Add: Room 826, 8F,BLDG 13, University Science Park(East), Zhengzhou City,P.R.Henan,China.Zip Code: 450051

Tel: 86-371-60911368

Email: info@global-antenna.com

Web: <https://www.global-antenna.com>