ZHENGZHOU LEHENG ELECTRONIC TECHNOLOGY CO.,LTD

617-6000 MHz 2×2 MIMO Pole / Wall Mount Panel Antenna

PN: GL660PB8XJ

Electrical Specifications

Frequency Range (MHz)	617-698	698-960	1710-2700	3300-4200	4900-6000
Gain (dBi)	5.5	6.0	7.0	8	8
Horizontal Half-power Beamwidth (°)	80	85	68	75	50
Vertical Half-power Beamwidth (°)	70	75	60	75	35
Polarization	±45°				
VSWR	≤1.8	≤1.8	≤1.8	≤1.8	≤2.0
Isolation (dB)	≥20	≥20	≥23	≥23	≥20
Front to Back Ratio (dB)	≥15	≥15	≥20	≥25	≥18
Average Power, Maximum (W)	50				
PIM(dBc)	-140@2×20W				
Impedance (Ω)	50				
Lightning Protection	DC Ground				

Mechanical Specifications

Dimensions (mm)	250×305×85
Net Weight (kg)	1
Radome Material and Color	ABS, White (RAL9003)
Cable Length (cm)	30
Connector	N Female (2×)

Environmental Specifications

Application	Indoor / Outdoor
Operating Temperature (℃)	-55 to +60
Humidity (%)	5 to 95

Mounting Specifications

Mounting Style	Pole / Wall Mount

MOUNTING ACCESSORIES ARE INCLUDED UNLESS OTHERWISE SPECIFIED



Add: Room 826, Floor 8,BLDG 13, University Science Park(East), Zhengzhou City,P.R.Henan,China. Zip Code: 450000

Tel: 86-371-60911368 Email: sales@global-antenna.com