




GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product type:Flexible Cable connectors/Straight Cable Plugs

Product number:GLSMP03

Frequency Range(GHz)	0-40	
Characteristic impedance(ohm)	50	
VSWR	≤1.15	
Insulation resistance	≥5000MΩ	
Dielectric Withstanding voltage	750V(rms)	
Voltage rating	250V(rms)	
Contact resistance	Center conductor	≤6mΩ
	Outer conductor	≤2mΩ
Connector	SMP	
Length(mm)	Φ 3.1*16.3	
Apply cable	2/50S	
Durability	500 Cycles	
MATERIAL AND PLATING		
Body	Brass or phosphor bronze,gold plated	
Male center contacts	phosphor bronze,gold plated	
Female center contacts	Beryllium copper,gold plated	
Insulators	PTFE	
Gaskets	Glass	
Crimp ferrules	Copper alloy,gold or nickel plated	
Temperature range	-65~+165℃	



Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.
Tel: 86-371-60911368 Email:info@global-antenna.com
Web:<http://www.asialeren.com> <http://www.global-antenna.com>