

# GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

4720-4920 MHz 5dBi 4-Lead Omnidirectional Antenna,N Female

PN: GLW49CM5Q

## Electrical Specifications

Frequency Range (MHz)	4720-4920
Bandwidth (MHz)	200
Horizontal Half-power Beamwidth (°)	360
MAX Gain (dBi)	5
Polarization	Vertical (4×)
VSWR	≤1.5
Isolation (dB)	≥ 25
Average Power, Maximum (W)	50
Impedance (Ω)	50



## Mechanical Specifications

Dimensions (mm)	Φ119×35
Net Weight (kg)	0.26
Radome Material	UV Resistant ABS
Radome Color	White
Cable Type	RG58/U
Cable Length (CM)	92 or Customized (4×)
Connector	N Female or Customized (4×)

## Environmental Specifications

Application	Indoor
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)
Ingress Protection	IP67
Humidity (%)	5 to 95

## Mounting Specifications

MOUNTING Accessories ARE INCLUDED UNLESS OTHERWISE SPECIFIED

Mounting Accessories	Threaded Bolt with Nut
----------------------	------------------------

## Special Note

/

**Add:** Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China. Zip Code: 450051

**Tel:** 86-371-60911368

**Email:** [sales@global-antenna.com](mailto:sales@global-antenna.com)

**Web:** <https://www.global-antenna.com>